



HOT MELT GLUE STICKS 11 MM

TRANSPARENT, HIGH- STRENGTH, ROUND SHAPED, 11 MM DIAMETER



PRODUCT DESCRIPTION

Transparent and high- strength hot melt glue sticks with a diameter of 11 mm for DIY work, repairing, fixing, sealing and insulating. Usable for all commercially available hot melt glue guns with Ø 11 mm glue sticks.

FIELD OF APPLICATION

Glues many porous and non porous materials in seconds such as wood, metal, stone, glass, tiles, ceramic, leather, textiles and many plastics. With a high melting capacity and is suited for DIY and all household repairs. Glues almost all materials quickly, neatly, permanently and reliably. Ideal for fixing, repairing, isolating and sealing. For example carpets, shoe soles and heels, mounting laths, skirting boards or glueing a loose tile. Multifunctional. Especially for do-it-yourself and semi-professional use.

Not suitable for PE, PP, PTFE, as well as heat sensitive materials. Supporting elements or objects permanently under tension.

PROPERTIES

- Transparent and high- strength
- Short setting time
- Weather resistant
- Temperature resistant up to +70 °C
- Does not shrink, does not age
- Solvent-free
- Resistant to UV-light, washing powders and detergents
- Good electrical insulating capacity
- Crack filling
- Ø 11 mm

PREPARATION

Surface Requirements: The areas to be glued must be dry and free of any dust or grease.

APPLICATION

Directions for use:

Apply the glue quickly, and not too sparingly. Stick the two pieces together immediately. Always apply the glue to the harder material. Glue application: on flexible surfaces, apply the glue in thick lines, on hard surfaces, you can apply the glue in thick lines or in dots. The glue can be used to fill small holes and cracks.

Stains/residue: Cured adhesive residue can only be removed mechanically.

Points of attention: Do not use at temperatures below +5 °C. Never remove glue sticks from glue gun, this could damage the mechanism.

TECHNICAL SPECIFICATIONS

| | |
|---------------------------------|---------------------------------|
| Chemical base: | Ethylene vinylacetate copolymer |
| Colour: | Transparent |
| Colour after curing/drying: | Transparent |
| Consistency: | Solid |
| Filling capacity: | Very good |
| Hardness (Shore A): | 80 |
| Insulating: | Good |
| Melting temperature Minimum: | 160 |
| Melting temperature Maximum: | 200 °C |
| Maximum temperature resistance: | 70 °C |
| Open time approx.: | 45 seconds |
| Solvent free: | Yes |

PACK SIZES

Available in: · 10 pieces · 24 pieces · 500 pieces

STORAGE CONDITIONS

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.